836 NORTH STREET, TEWKSBURY, MASSACHUSETTS 01876, TEL.(617) 851-4111, TWX 710 343-6769, TELEX 94-7421

The Model 2222 Alphanumeric Keyboard is a peripheral to the WANG System 2200. Resembling a typewriter keyboard, it lends itself easily to those users who are familiar with a selectric typewriter keyboard or to those users requiring large amounts of alpha input. Each BASIC language word or symbol is keyed-in one character at a time.

The 2222 Keyboard is divided into four major zones; each zone is designed to perform certain functions (see photo on reverse side).

Zone 1, which is very similar to a selectric typewriter key-board, contains all the upper and lowercase alpha characters, the 0 through 9 numeric characters, along with punctuation, arithmetic and special characters. The ALPHA CONTROL SWITCH located on the lefthand side of zone 1 enables the user to lock the alpha characters set into the uppercase mode, for entering BASIC programs.

Zone 2 contains the 0 - 9 numeric keys, decimal point, arithmetic operations, trigonometric functions, and the PRINT key. Zone 2 is generally considered a "scratch pad" calculator.

Zone 3 contains keys for program control and execution, namely RESET (resets program), HALT/STEP (halts program execution), LINE ERASE (erases an entire line), RUN (executes a program in the memory of the system).

Zone 4 consists of 16 user-defined special function keys for defining and accessing up to 32 subroutines either manually or under program control, or defining up to 32 custom text entries.





SPECIFICATIONS

Character Set

Complete IBM Selectric character set.

Size

Weight

7 lbs. (3.2 kg)

Connecting Cables

12 ft (3.66 m) cable with connector to CPU I/O jack

Operating Environment

 50° F to 90° F (10° C to 32° C) 40% to 60% relative humidity

System 2200 Power Requirements

115 or 230 VAC ± 10% 50 or 60 Hz ± ½ cycle Standard warranty applies.

ORDERING SPECIFICATIONS

An input keyboard enabling the input of alphanumeric instructions directly into the WANG System 2200. Character set must include complete set of control instructions which, when entered, directs the system to perform program operation control functions. The keyboard must also be usable for data input to the System 2200.

ZONE 4



ZONE 1 ZONE 2 ZONE 3

Wang Laboratories reserves the right to change specifications without prior notice.



LABORATORIES, INC.